



KH/KA

SINGLE-PHASE **HYBRID/AC INVERTER**



HIGH VOLTAGE

Includes high-voltage batteries for maximum round-trip efficiency.



EASY INSTALLATION

Flexible configuration, plug and play set-up, built-in fuse protection.



IP65 RATED

Engineered to last with maximum flexibility. Suitable for outdoor installation.



REMOTE MONITORING

Monitor your system remotely via smartphone app or web portal.



Advanced System Monitoring
with **FoxCloud V2.0**

REFINED – POWERFUL – FLEXIBLE

Harness the power of the sun day and night with the ground-breaking range of Hybrid & AC inverter from Fox ESS. Full of advanced features and compatible with our very own range of high-voltage batteries, the hybrid range from Fox ESS.

7kW ...>> 10.5kW



For more information about the Fox ESS range, visit:
www.fox-ess.com



up to
10.5kW
charge/
discharge

TECHNICAL SPECIFICATIONS

MODEL	KH7 KA7	KH8 KA8	KH9 KA9	KH10 KA10	KH10.5 KA10.5
ELECTRICAL CHARACTERISTICS					
Battery Type	Li-Ion				
Battery Voltage Range [V]	85 ~ 480				
Recommended Battery Voltage [V]	300				
Max. Charge Current [A]	50				
Max. Discharge Current [A]	50				
Communication Interfaces	CAN / RS485				
Reverse Connect Protection	YES				
INPUT PV (FOR KH ONLY)					
Max. Array Power [Wp]	15000	16000	18000	20000	21000
Max. Input Power [W]	10500	12000	13500	15000	15000
Max. DC Voltage [V]	600				
Norminal DC Operating Voltage [V]	360				
Max. Input Current (Input A / Input B) [A]	16 / 16 / 16	16 / 16 / 16	16 / 16 / 16 / 16	16 / 16 / 16 / 16	16 / 16 / 16 / 16
Max. Short Circuit Current (Input A / Input B) [A]	20 / 20 / 20	20 / 20 / 20	20 / 20 / 20 / 20	20 / 20 / 20 / 20	20 / 20 / 20 / 20
Max. Inverter Backfeed Current to the Array [mA]	0				
MPPT Voltage Range [V]	80 ~ 500				
Start-up Voltage [V]	75				
No. of MPP Trackers	3	3	4	4	4
Strings Per MPP Tracker	1				
DC Disconnection Switch	Optional				
OUTPUT AC					
Norminal AC Power [VA]	7000	8000	9000	10000	10500
Max. Apparent AC power [VA]	7700	8800	9900	10500	10500
Rated Grid Voltage (AC Voltage Range) [V]	220 / 230 / 240 (180 ~ 270)				
Rated Grid Frequency [Hz]	50 / 60, ±5				
Norminal AC Current [A]	30.4	34.8	39.1	43.5	45.7
Max. AC Current [A]	33.5	38.3	43.0	45.7	47.7
Displacement Power Factor	0.8 Leading to 0.8 Lagging				
Total Harmonic Distortion (THDi, Rated Power) [%]	<3				
INPUT AC					
Max AC Power [VA]	14000	16000	18000	18000	18000
Max. AC Current [A]	60.9	69.6	78.3	78.3	78.3
Rated Grid Voltage (AC Voltage Range) [V]	220 / 230 / 240 (180 ~ 270)				
Rated Grid Frequency [Hz]	50 / 60, ±5				
EPS OUTPUT (WITH BATTERY)					
Max. EPS Power [VA]	7000	8000	9000	10000	10500
EPS Rated Voltage [V], Frequency [Hz]	220/230/240, 50 / 60				
Max. EPS Current [A]	31.8	36.4	40.9	45.5	47.7
EPS Peak Power (60s) [W]	10000	10000	12000	12000	12000
Switch Time [ms]	<20				
Total Harmonic Distortion (THDv, Linear Load) [%]	<2				
Parallel Operation	Yes @max10PCS				
EFFICIENCY					
MPPT Efficiency [%]	99.90				
Euro-Efficiency [%]	97.40				
Max. Efficiency [%]	97.80				
Max. Battery Charge Efficiency (PV to BAT) (@Full Load) [%]	98.50				
Max. Battery Discharge Efficiency (BAT to AC) (@Full Load) [%]	97.00				
PROTECTION					
PV Reverse Polarity Protection	YES				
Battert Reverse Protection	YES				
Anti-islanding Protection	YES				
Output Short Protection	YES				
Leakage Current Protection	YES				
Insulation Resistor Detection	YES				
Over-current Protection / Over-temperature Protection	YES				
Over Voltage Category	III (AC side), II (DC side)				
AC/DC Surge Protection	Type II / Type II				
AFCI Protection	Optional				
POWER CONSUMPTION					
Standby Consumption [W] (Ldle)	<15				
STANDARD					
Safety	IEC62109-1 / IEC62109-2 / IEC 62477-1				
EMC	EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3				
Cetification	G99 / EN50549 / NRS 097-2-1				
ENVIRONMENT LIMIT					
Ingress Protection	IP65				
Protective Class	Class I				
Operating Temperature Range [°C]	-25 ~ +60 (Derating at +45)				
Humidity [%]	0 ~ 95 (Non-condensing)				
Altitude [m]	<2000				
Storage Temperature [°C]	-40 ~ +70				
Noise Emission (Typical) [dB]	<30				
DIMENSION AND WEIGHT					
Dimensions (W * H * D) [mm]	450*527*208				
Weight [kg]	29 (KH) / 27.5 (KA)				
Cooling Concept	Natural				
Topology	Non-isolated				
Communication	Meter(Optional), WIFI, 4G (Optional), DRM, USB, CT, RS485				
LCD Display	Backlight 16*4 Character				

* More technical characteristics are available on demand and customized.