



H1(G2)/AC1(G2)

SINGLE-PHASE **HYBRID/AC INVERTER**



HIGH VOLTAGE

Includes high-voltage batteries for maximum round-trip efficiency.



EASY INSTALLATION

Flexible configuration, plug and play set-up, built-in fuse protection.



IP65 RATED

Engineered to last with maximum flexibility. Suitable for outdoor installation.



REMOTE MONITORING

Monitor your system remotely via smartphone app or web portal.



Advanced System Monitoring
with **FoxCloud V2.0**

REFINED – POWERFUL – FLEXIBLE

Harness the power of the sun day and night with the ground-breaking range of Hybrid & AC inverter from Fox ESS. Full of advanced features and compatible with our very own range of high-voltage batteries, the hybrid range from Fox ESS.

3kW ...>> 6kW



For more information about the Fox ESS range, visit:
www.fox-ess.com



up to
6kW
charge/
discharge

TECHNICAL SPECIFICATIONS

MODEL	H1-3.0-E-G2 AC1-3.0-E-G2	H1-3.7-E-G2 AC1-3.7-E-G2	H1-4.6-E-G2 AC1-4.6-E-G2	H1-5.0-E-G2 AC1-5.0-E-G2	H1-6.0-E-G2 AC1-6.0-E-G2
INPUT PV (ONLY FOR HYBRID)					
Max. Array Power [Wp]	6000	7400	9200	10000	12000
Max. Input Power [W]	4500 A:2250 B:2250	5500 A:2750 B:2750	6900 A:3450 B:3450	7500 A:3750 B:3750	9000 A:4500 B:4500
Max. Input Voltage [V]	600				
Start-up Input Voltage [V]	75				
Rated Input Voltage [V]	360				
MPPT Operating Voltage Range [V]	80 ~ 550				
Max. Input Current [A]	16 / 16				
Max. Short-circuit Current [A]	20 / 20				
No. of Independent MPP Trackers	2				
No. of Strings per MPP Tracker	1				
BATTERY CONNECTION					
Battery Type	Lithium Battery (LFP)				
Battery Voltage [V]	80 ~ 480				
Max. Charge/Discharge Current [A]	40				
Communication Interface	CAN(communicate with inverter, upgrade BMS)				
AC INPUT AND OUTPUT (GRID)					
Max. AC Input Power [VA]	6000	7680	9200	10000	12000
Max. AC Input Current (per phase) [A]	27.3	34.9	41.8	45.5	54.5
Rated Output Power [W]	3000	3680	4600	5000	6000
Max. Output Apparent Power [VA]	3300	4048/3680 ¹	5060	5500	6600
Rated Output Current (per phase) [A]	13.6	16.7/16 ¹	20.9	22.7	27.3
Rated Output Current (per phase) [A](For AUS)	13.0	16.0	20.0	21.7	26.1
Max. Output Current [A]	15.0	18.4	23.0	25.0	30.0
Rated Grid Voltage [V]	220/230/240				
Rated Grid Frequency [Hz]	50/60				
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)				
THDi [%]	<3 @rated power				
EPS OUTPUT (WITH BATTERY)					
Max. Output Apparent Power [VA]	3000	3680	4600	5000	6000
Peak Output Apparent Power (60s) [VA]	3600	4400	5500	6000	7200
Max. Current (per phase) [A]	13.6	16.7	20.9	22.7	27.3
Rated Output Voltage [V]	220/230/240				
Rated Output Frequency [Hz]	50/60				
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)				
THDv (linear Load) [%]	<2 @rated power				
Parallel operation [PCS]	10				
Switch time [ms]	<20				
EFFICIENCY					
Euro Efficiency [%]	95.26	95.70	96.23	96.30	96.33
Max. Efficiency [%]	97.01	97.08	97.04	97.08	97.08
Max. Battery Charge Efficiency (PV to BAT) (@full load) [%]	98.50				
Max. Battery Discharge Efficiency (BAT to AC) (@full load) [%]	97.00				
PROTECTION					
Insulation Monitoring	YES				
Residual Current Monitoring	YES				
DC Reverse Polarity Protection	YES				
Anti-islanding Protection	YES				
AC Short-circuit Protection	YES				
AC Overcurrent/Overvoltage Protection	YES				
DC Switch	YES				
Battery Wake-up Function	YES				
SPD	DC: Type II /AC: Type III				
AFCI	Optional				
GENERAL DATA					
Dimensions (W*H*D) [mm]	434*418*185				
Weight [kg]	22				
Installation	Wall-Mounted				
Topology	Non-isolated				
Cooling Method	Natural				
Noise Emission [dB]	35				
Max. Operating Altitude [m]	2000				
Operating Temperature Range [°C]	-25 ~ 60				
Humidity (No Condensation) [%]	0 ~ 100				
Ingress protection	IP65				
Standby consumption[W]	< 15				
Monitoring Module	WiFi, LAN(Optional) , 4G(Optional)				
Communication	RS485, DRM, Ripple Control, USB, CAN				
Display	LCD, App, Website				
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)					
Safety	EN 62109-1, EN 62109-2				
Grid Regulation	G98, G99, EN50549, AS / NZS 4777.2				

* More technical characteristics are available on demand and customized.

1. 3680 for G98.