



Smart LAN

SMART L 3.0

REMOTE MONITORING



- Stable lan communication
- Vodafone, Tata, Aircel and Airtel compatible
- Clean and compact design
- User-friendly monitoring App
- Monitor your system from anywhere
- 24/7 monitoring



EASY INSTALLATION

plug and play installation.



IP65 RATED

Suitable for outdoor installation.



STRONG SIGNAL

Strong LAN signal for maximum range.



REMOTE MONITORING

Connect to the Fox ESS Cloud.

The Smart L 3.0 is an intelligent LAN enabled device allowing you to monitor the status and performance of your Fox ESS PV system via the Fox ESS Cloud remote monitoring platform. The Smart L3.0 is ideal in situations where there is no reliable WiFi or GPRS connection available.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.



For more information about the Fox ESS range, visit
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	Smart L 3.0
Dimensions (L*W*H) [mm]	100*49*28
Weight [g]	55
Input Voltage [V]	DC7 ~ 12
Max. Power [W]	1
Ethernet Speed [M]	10/100
Interface	RS485
Parameter	9600/8/n/1(default)
Green LED	Receive Data from Inverter
Red LED	Work status
connector	USB
Temperature	-20 ~ 60
Humidity [%]	0 ~ 95 (no condensation)
Altitude [M]	≤4000
Ingress Protection	IP65
Fire rating	UL94V-0
UV immunity	F1

